



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 413 356 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
28.04.2004 Bulletin 2004/18

(51) Int Cl.⁷: **B01J 35/04, F01N 3/022**

(21) Application number: **03256383.5**

(22) Date of filing: **09.10.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**
Designated Extension States:
AL LT LV MK

(72) Inventors:
• Kai, Ryuji c/o Intell. Prop. Dept.
Nagoya-shi Aichi-ken 467-8530 (JP)
• Yamada, Toshio c/o Intell. Property Dept.
Nagoya-shi Aichi-ken 467-8530 (JP)

(30) Priority: **10.10.2002 JP 2002297713**

(74) Representative: **Paget, Hugh Charles Edward et al
MEWBURN ELLIS
York House
23 Kingsway
London WC2B 6HP (GB)**


(71) Applicant: **Ngk Insulator, Ltd.
Nagoya-shi, Aichi 467-8530 (JP)**

(54) **Filtering honeycomb structure with voids, method for its manufacturing, and its use in exhaust gas purification system**

(57) There is disclosed a honeycomb structure which can be used as a filter for trapping/collecting particulates included in an exhaust gas and in which it is possible to remove ashes deposited inside without requiring any special mechanism or apparatus or without being detached from the exhaust system. The structure comprises a plurality of through channels 9 extending to an axial direction of a honeycomb structure, porous

partition walls 7 separating through channels one another, and plugging portions 11; said plugging portion plugging predetermined through channels 9a at one end and the rest of through channels 9b at other end opposite to the plugged end of the predetermined through channels, wherein at least a part of predetermined crossing portions of the porous partition walls is discontinued to form a void portion 17 in each of the predetermined crossing portions.

FIG. 1



EP 1 413 356 A1

Description

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to a honeycomb structure for use in a filter for trapping/collecting particulates in an exhaust gas of an internal combustion engine, boiler, and the like, a method for manufacturing the honeycomb structure, and an exhaust gas purification system using the honeycomb structure.

Description of the Related Art

[0002] An exhaust gas exhausted from internal combustion engines such as a diesel engine contains a large amount of particulates (particulate materials) containing carbon which causes pollution as a major component. Therefore, a filter for trapping/collecting the particulates is sometimes mounted in an exhaust system.

[0003] In general, as a filter to be used for this purpose, as shown in FIG. 8 (a) and FIG. 8 (b), one usually uses a honeycomb structure including a plurality of through channels 9, porous partition walls 7 separating through channels one another; said through channels extending to an axial direction of the honeycomb structure, and plugging portions 11 plugging the predetermined through channels 9a at one end face, and the rest of the through channels 9b at other end opposite to the plugged end of the predetermined through channels 9a.

[0004] The exhaust gas flows in the filter made of such a honeycomb structure mentioned above via one end face 3 thereof, and the gas flows out of the other end face 5 after the particulates included in the gas are removed. Concretely, the exhaust gas first flows in the through channels 9b whose ends are not plugged at the end face 3 on an inflow side and whose other ends are plugged at the end face 5 on an outflow side, moves through the porous partition walls 7 into the through channels 9a whose ends are plugged in the inflow-side end face 3 and whose other ends are not plugged in the outflow-side end face 5, and flows out via the through channels 9a. Moreover, in this case, the partition walls 7 function as filter layers, and the particulates in the gas are captured by the partition walls 7 and deposited on the partition walls 7.

[0005] After the use of the filter for a given period of time, the particulates deposited in the filter are burned with heating the filter by electric conduction of an electric heater to be removed, but are not completely removed, and some of the particulates remain as ashes (ash component) within the filter. Therefore, with the use of the filter over a long period of time, a filter capacity substantially decreases by the deposition of the ashes, pressure loss increases, and an amount of particulates to be trapped/collected decreases. There has therefore been a problem that frequency for regeneration treatment of the filter by burning/removing the captured particulate materials as described above have to be increased.

[0006] To solve the problem, for example, there has been proposed an apparatus in which the filter is supported in a direction vertical to the direction of the gas flow, and said apparatus having a vibration device provided to the filter, and an ash collecting portion provided at lower portion of the filter for collecting the ashes dropping off the filter by virtue of vibration applied to the filter by the vibration device (see JP-A-8-28247).

[0007] Moreover, there has been proposed a method in which a highly pressurized fluid such as water is sprayed onto one end of the filter to clean/remove the residue after burning resided in the filter (see JP-A-2001-50028).

[0008] Furthermore, there has been proposed a device for discharging ashes with employing a filter a part of whose partition walls has been removed (see Japanese Utility Model Application Laid-Open No. 60-112618).

[0009] However, any one of those techniques proposed has not been very practical. For example, the device proposed in the above-mentioned Laid-open Japanese Utility Model application can not be used practically since a trapping/collecting efficiency of particulates during the use is low because the hole portion formed by removing a part of the partition wall was apt not to be closed. Moreover, a special mechanism or apparatus is required to remove the ashes from the filter in some case, or the filter needs to be detached tentatively from the exhaust system to remove the ashes from the filter in the other case. Therefore, the conventional apparatus or method has not been practical.

SUMMARY OF THE INVENTION

[0010] The present invention has been completed in consideration of such conventional situations, and an object thereof is to provide a honeycomb structure capable of using as a filter for trapping/collecting particulates included in an exhaust gas with removing ashes deposited inside without requiring any special mechanism or device or without being detached from an exhaust system.

[0011] According to the present invention, there is provided a honeycomb structure comprising: a plurality of through channels extending to an axial direction of a honeycomb structure, porous partition walls separating from one another,

and plugging portions; said plugging portions plugging the predetermined through channels at one end thereof and the rest of through channels at other end opposite to the plugged end of the predetermined through channels, wherein at least a part of crossing portions of predetermined porous partition walls is discontinued to form a void portion in each of the predetermined crossing portions (first aspect of the invention).

[0012] Hereinafter, the expression "void portion" is used in the present specification to mean a (the) void portion formed in the portion where the partition walls were to have crossed at a predetermined angle.

[0013] Moreover, according to the present invention, there is provided a method for manufacturing the honeycomb structure according to the first aspect of the invention, comprising the steps of: preparing a die for extrusion molding of a honeycomb structure capable of extruding a honeycomb structure having a plural number of void portions in partition walls at a predetermined position, and extruding a honeycomb structure having an intended structure using said die (second aspect of the invention).

[0014] Furthermore, according to the present invention, there is provided an exhaust gas purification system for trapping/collecting/removing particulate materials containing carbon as a major component included in dust-containing fluids such as an exhaust gas of an internal combustion engine, the system comprising: the honeycomb structure according to the first aspect of the invention, which is used as a filter for trapping/collecting the particulate materials; and heating means for burning the particulate materials trapped/collected by the honeycomb structure to regenerate a filtering capacity, wherein void portions in partition walls of the honeycomb structure have such a structure that the void portions are substantially closed due to the accumulation of trapped/collected particulate materials during practical use, thus closed void portions are substantially reopened when the captured particulate materials are burnt by heating the filter at the time of the regeneration, and at least some of unburnt materials such as ashes deposited in the honeycomb structure are discharged via the reopened void portions from the honeycomb structure with flow of dust-containing fluids, when the void portions are reopened (third aspect of the invention).

BRIEF DESCRIPTION OF THE DRAWINGS

[0015]

FIG. 1 is a schematic plan view showing one example of an embodiment of a honeycomb structure according to a first aspect of the invention as seen from an end-face side;

FIG. 2 is a partial plan view showing that a void portion is closed by particulates;

FIG. 3 is a partial plan view showing that the void portion is open;

FIG. 4 is a schematic diagram showing one example of arrangement of void portions;

FIG. 5 is a schematic diagram showing another example of the arrangement of the void portions;

FIG. 6 is a schematic diagram showing an example in which a thickness of a partition wall is changed;

FIG. 7 is an explanatory view for defining terms "gap" and "gap width" in the present invention;

FIG. 8 (a) and FIG. 8 (b) show schematic explanatory views showing a basic structure of the honeycomb structure for use as a conventional filter, FIG. 8(a) is a plan view seen from one end face side, and FIG. 8(b) is a sectional view;

FIG. 9 is a graph showing changes of pressure loss of DPF by a run time in a case in which particulates are repeatedly trapped/collected to regenerate the filter;

FIG. 10 is a graph showing changes of a trapping/collecting efficiency with the elapse of the run time; and

FIG. 11 is a graph showing a relation between the gap width of the void portion and the trapping/collecting efficiency in a given run time.

[0016] The following numerical references in the accompanying drawings denote the portion and/or the member as specified below, respectively: 3...end face from which the exhaust gas flows in, 5...end face from which the exhaust gas flows out, 7... partition wall, 9... through channel, 9a...through channel, 9b...through channel, 11 ...plugging portion, 17...void portion in crossing portion, 21... particulates.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0017] FIG. 1 is a schematic plan view showing one example of an embodiment of a honeycomb structure according to a first aspect of the invention as seen from an end-face side. A basic structure of the honeycomb structure according to the first aspect of the invention includes: a plurality of through channels 9 extending to an axial direction of a honeycomb structure, porous partition walls 7 separating through channels one another and plugging portions 11; said plugging portions plugging predetermined through channels 9a at one end, and the rest of through channels 9b at other end opposite to the plugged end of the predetermined through channels 9a.

[0018] Moreover, as a common characteristic structure, there is formed a void portion 17 each in at least a part of each of the predetermined crossing portions of porous partition walls 7.

[0019] When the honeycomb structure constituted in this manner is used as a filter for trapping/collecting particulates included in an exhaust gas of internal combustion engines such as a diesel engine, some of the particulates in the exhaust gas pass through the void portions 17 at a stage immediately after the initiation of the practical run as a filter. Therefore, as compared with a conventional filter having no void portion, a trapping/collecting efficiency drops at this stage. However, as shown in FIG. 2, since trapped/collected particulates 21 are deposited, the void portions 17 are substantially brought into closed states in a short time. Thereafter, the same degree of the trapping/collecting efficiency as that of the conventional filter can be attained.

[0020] Subsequently, when a given amount of trapped/collected particulates 21 are deposited in the filter, a regeneration treatment is carried out by burning/removing the captured particulates 21 with heating the filter by a heater, and the like. By this regeneration treatment, as shown in FIG. 3, the void portion 17 plugged with the captured particulates returns again to a substantially open state.

[0021] When the void portion 17 becomes an opened state in this manner, residual ashes formed as a result of burning the captured particulates in the filter are discharged to the outside via the void portion 17 with a flow of the exhaust gas, and the filter returns to a clean state substantially equal to that at the time of initiating to use the honeycomb structure as a filter. When a series of cycle "the trapping/collecting of the particulates → the burning/removing of the captured particulates by the regeneration treatment → the discharging of the residual ashes" is repeated in this manner, the ashes deposited inside can be removed without requiring any special mechanism or apparatus or without temporarily detaching the filter from an exhaust system for removal of particulates, in the case of the present honeycomb structure.

[0022] In the honeycomb structure according to the first aspect of the invention, the void portions 17 are preferably formed along the whole length of the honeycomb structure so as to smoothly discharge the ashes when the void portions 17 are reopened. Moreover, as shown in FIGS. 4 and 5, the void portions 17 are preferably regularly arranged/formed at predetermined crossing portions of partition walls, thereby fluctuations of strength in each portion of the honeycomb structure can be reduced.

[0023] A gap width in the void portion 17 is preferably 0.2 to 1 mm, more preferably 0.4 to 0.8 mm. It is to be noted that the expression "the gap in the void portion" in the present specification and the accompanying claims means a cut portion formed between two partition walls 7 to be crossed to partition the through channel 9 of FIG. 7 due to the formation of the void portion 17 as shown in FIG. 7. The "gap width" refers to a diameter of a minimum circle (minimum inscribed circle) S inscribed with the gap in the void portion in the plane vertical to the extending direction of the through channel 9.

[0024] When the gap width is less than 0.2 mm, it is sometimes difficult to discharge the ashes even in the reopened state of the void portions 17. On the other hand, when the gap width exceeds 1 mm, a long time is required until the trapped/collected particulates 21 plug the void portions sufficiently, and the trapping/collecting efficiency largely drops at this time.

[0025] When there are present void portions 17 in the crossing portion of partition walls as described above, the trapping/collecting efficiency temporarily drops just after the initiation of the run or the regeneration treatment as compared with the honeycomb structure having no void portion. However, when the gap in the void portion 17 is set to the above-described range, the void portion 17 is closed due to the deposition of the particulates 21 within a short time. Therefore, there is no practical problem, when the average trapping/collecting efficiency in the run for a given period of time is taken into consideration, since the difference in the efficiency between the honeycomb structure having the void portions 17 and the one having no void portion is slight.

[0026] When the honeycomb structure according to the first aspect of the invention is used for the filter for trapping/collecting the particulates included in the exhaust gas of the internal combustion engine, the filter is usually disposed in the exhaust gas system in such a manner that the center of an exhaust gas flow passes through the central portion of the section of the honeycomb structure. Therefore, as compared with the flow speed of the exhaust gas in the central portion, that of the exhaust gas flowing at the vicinity of an outer peripheral portion of the honeycomb structure tends to be slow.

[0027] If there is a portion wherein the flow speed of the exhaust gas is slow as mentioned above, the ashes in the portion wherein the flow speed of the exhaust gas is slow are not easily discharged as compared with those in the other portions. Therefore, instead of setting all the gap widths of the void portions to be uniform, the gap widths may substantially be set to be nonuniform, in accordance with the flow speed of the exhaust gas in each portion. For example, in the above-described example, the flow speed of the exhaust gas at the vicinity of the outer peripheral portion of the honeycomb structure decreases. Therefore, it is preferable to set the gap width in the void portions in the slower flow speed portion larger than that of the void portion in the central portion seen from the side of an end face of the honeycomb structure, so that the ashes are easily discharged.

[0028] Moreover, in the first aspect of the invention, in order to enhance strength (isostatic strength) of the honeycomb structure as a whole, the thickness of the partition walls having no void portion and extending to the predetermined direction without having the discontinued portions is 1.05 to 1.5 times, more preferably 1.1 to 1.3 times that of the

partition walls having the void portion and consequently having the discontinued portion in the crossing portions of partition walls crossing at right angles each other to the length direction of the honeycomb structure.

[0029] For example, in the embodiments shown in FIGS. 4 and 5, in the section of the honeycomb structure crossing at right angles to the length direction, the thickness T_2 of the partition wall having no void portion 17 and extending without having discontinued portion in an X-direction (lateral direction of the drawing) is set to be larger than the thickness T_1 of the partition wall having the void portion 17 and discontinued portion defined by the void portion 17. By employing this constitution, the strength of the honeycomb structure in the X-direction can be enhanced.

[0030] Moreover, as shown in FIG. 6, the thickness T_2 of the partition wall having no void portion 17 extending to the X-direction (lateral direction of the drawing) without having discontinued portion is set to be larger than the thickness T_1 of the partition wall having the void portion 17 and discontinued portion defined by the void portion 17. Furthermore, the thickness T_4 of the partition wall having no void portion 17 and extending to the Y-direction (longitudinal direction of the drawing) without having discontinued portion may also be set to be larger than the thickness T_3 of the partition wall having the void portion 17 and discontinued portion defined by the void portion 17. In this case, the strengths of the honeycomb structure in both the X and Y-directions can be enhanced.

[0031] If thickness T_2 , T_4 of the partition wall having no void portions 17 and extending to the predetermined direction without having discontinued portion is less than 1.05 times the thickness T_1 , T_3 of the partition wall having the void portion 17 and discontinued portion defined by the void portion 17, the strength enhancement effect of the honeycomb structure is low. On the other hand, if exceeds 1.5 times, a difference is generated in a through resistance of the exhaust gas between the thickened partition wall and the not-thickened partition wall, and the pressure loss or the trapping/collecting efficiency of the particulates is sometimes adversely affected.

[0032] A sectional shape (cell shape) of the through channel is not especially limited, but from a viewpoint of manufacturing, any shape of a triangular shape, a quadrangular shape, a hexagonal shape, and circular shape is preferable. When the sectional shape of the through channel is the quadrangular shape, it is preferable to form the void portions 17 regularly at every other crossing portion of partition walls in the crossing portions of partition walls disposed adjacent to one another as shown in FIG. 4 or 6. Moreover, it is preferable to have only one gap formed by the void portion 17 in each of predetermined through channels 9, from a viewpoint of balancing the strength of the honeycomb structure or easiness of discharging the ashes. Furthermore, the sectional shape of the honeycomb structure is not especially limited. In addition to the circular shape, any shape can be used such as an elliptic shape, oblong shape, oval shape, substantially triangular shape, substantially quadrangular shape, and another polygonal shape.

[0033] For a material of the honeycomb structure, from a viewpoint of strength or heat resistance, any one having as a major crystal phase selected from the group consisting of cordierite, silicon carbide, silicon nitride, alumina, mullite, and lithium aluminum silicate (LAS) is preferably used. It is preferable to form the plugging portion from the same material as that of the honeycomb structure because the coefficients of thermal expansion of them coincide each other.

[0034] Application of the honeycomb structure according to the first aspect of the invention is not especially limited. As described above, however, it is most preferable to use it as a filter, with utilizing a filtering capacity of partition walls for separating through channels, for trapping/collecting/removing the particulates (particulate materials) included in dust-containing fluids such as the exhaust gas of the internal combustion engine, thereby the characteristics of the structure can be fully utilized.

[0035] Next, a method for manufacturing the honeycomb structure according to the present invention will be described noting the formation of the void portions which are characteristic portions of the honeycomb structure.

[0036] In the method for manufacturing the honeycomb structure according to a second aspect of the invention, one should prepare a die for extruding a honeycomb structure having an intended construction. One possible preparation way is to close the predetermined crossing portions of the slits for forming partition walls in a die for extruding/molding a honeycomb structure to form the void portions as intended at the time of the extruding/molding of a honeycomb structure. The other preparation way is to form a new die having the intended slits so as to have a honeycomb structure having a predetermined shape inclusive of the void portions in the predetermined crossing portions of the partition walls.

[0037] In the present method, simultaneously with the extruding/molding of the honeycomb structure, the void portions can be formed. Therefore, this method is preferable from viewpoints of ease and economic efficiency, for example, as compared with a method of preparing a usual honeycomb structure including no void portion and subsequently forming the void portion by means such as mechanical processing.

[0038] An exhaust gas purification system according to a third aspect of the invention is constituted using the honeycomb structure according to the first aspect of the invention, and is used for a purpose of trapping/collecting/removing the particulates (particulate materials) containing carbon as a major component included in dust-containing fluids such as the exhaust gas of the internal combustion engine. This system includes: the honeycomb structure for use as the filter for trapping/collecting the particulates according to the first aspect of the invention; and heating means for burning the particulates trapped/collected by the honeycomb structure to regenerate the filtering capacity.

[0039] In this system, the void portions of the honeycomb structure are substantially closed by the trapping/collecting and depositing of the particulates, however, the closed void portions is reopened by burning particulates with heating

the filter at the time of the regeneration, and at least some of unburnt materials such as ashes deposited in the honeycomb structure are discharged from the honeycomb structure with the flow of the dust-containing fluids, when the void portions are reopened.

[0040] As the heating means of the system, it is preferable to use any one of an electric heater, a burner using a gas or liquid fuel, a microwave generation apparatus, and heating means for discharging unburnt fuel components in the exhaust gas of the internal combustion engine and for burning the unburnt fuel components by a catalytic reaction to raise an exhaust gas temperature.

Examples

[0041] The present invention will be described hereinafter in more detail based on examples, but the present invention is not limited to these examples in any means.

[Change of Pressure Loss with Elapse of Run Time]

[0042] A honeycomb structure having a diameter of 144 mm, a length of 152 mm, a partition wall thickness of 0.3 mm, and a cell density of 46/cm² was used to prepare a diesel particulate filter (DPF) of the conventional structure in which one end of the through channels was plugged by the plugging portion as shown in FIG. 8 (a) and FIG. 8 (b).

[0043] This DPF was mounted in an exhaust system of an in-line four-cylinder common rail type direct-injection diesel engine having a displacement of 2000 cc, and the trapping/collecting of the particulates and the regeneration were repeatedly carried out. It is to be noted that in the regeneration of the DPF, the fuel injected into an engine combustion chamber by post injection was burnt by a honeycomb type oxide catalyst disposed upstream the DPF, and the particulates deposited in the DPF were burned by the generated heat.

[0044] FIG. 9 shows changes of the pressure loss of DPF by a run time in a case in which the particulates are repeatedly trapped/collected to regenerate the filter. First, with an elapse of run time (with the trapping/collecting of the particulates), the pressure loss of the DPF rises. When the loss reaches preset ΔP_{\max} , the regeneration of the DPF is started. After a given time, the regeneration is ended. At this time, the pressure loss drops to ΔP_{\min} . Thereafter, the trapping/collecting of the particulates are started again.

[0045] When the steps of the trapping/collecting and the regenerating are repeated, and when the DPF is always completely regenerated at the time of the regeneration, ΔP_{\min} does not change. However, in the DPF including the conventional structure, ΔP_{\min} gradually rises by the deposition of unburnt components by the use over a long period. By the increase of ΔP_{\min} , a period between the regeneration and the next regeneration (regeneration interval = T) gradually shortens, and there occurs a necessity of frequently regenerating the filter. As a result, deterioration of a regeneration system is accelerated, usability such as a restriction on a run condition at the time of the regeneration is deteriorated, or defects such as deterioration of fuel consumption involved in the regeneration are generated. Moreover, in the run with a fixed regeneration interval, both the ΔP_{\min} and ΔP_{\max} rise, and therefore engine capability is deteriorated.

[Presence/Absence of Void portion and Trapping/Collecting Efficiency]

[0046] The honeycomb structure having the diameter of 144 mm, length of 152 mm, partition wall thickness of 0.3 mm, and cell density of 46/cm² was used to prepare a DPF (the void portions are not formed) including the conventional structure in which one end of the through channel was plugged by the plugging portion as shown in FIG. 8 (a) and FIG. 8 (b). Similarly, a DPF according to the present invention was prepared in which one end of the through channel was plugged by the plugging portion and the void portions were formed as shown in FIG. 1.

[0047] These two DPFs were mounted respectively in the exhaust system of the common rail type direct-injection diesel engine in the same manner as described above, the particulates were trapped/collected, and changes of the trapping/collecting efficiency with the elapse of the run time were checked. It is to be noted that for the trapping/collecting efficiency, a part of the exhaust gas was sucked and passed through filter paper, and a mass of soot in the exhaust gas, attached onto the filter paper, was measured and obtained by the following equation.

$$\text{Trapping/collecting efficiency (\%)} = \{1 - (\text{soot mass in DPF downstream}) / (\text{soot mass in DPF upstream})\} \times 100 \quad [\text{Equation 1}]$$

[0048] Results are shown in FIG. 10. Even in the DPF having the conventional structure in which no void portions are formed, the trapping/collecting efficiency immediately after the particulates start to be trapped/collected is low. The

trapping/collecting efficiency tends to rise with the increase of the trapped/collected amount with the elapse of time. On the other hand, in the DPF according to the present invention in which the void portions are formed, the exhaust gas flows out of the void portions as such. Therefore, the trapping/collecting efficiency immediately after the trapping/collecting starts is lower than that of the DPF including the conventional structure. However, when the void portions are closed by the deposited particulates, the trapping/collecting efficiency accordingly moderately rises. When the void portions are completely closed, the trapping/collecting efficiency thereof becomes equal to that of the conventional DPF.

[Gap Width of Void portion and Trapping/Collecting Efficiency]

[0049] The honeycomb structure having the diameter of 144 mm, length of 152 mm, partition wall thickness of 0.3 mm, and cell density of 46/cm² was used to prepare DPFs in which the void portions having various gap widths of 0 mm (the void portion is not formed) to 1.2 mm were formed.

[0050] These DPFs were mounted respectively in the exhaust system of the common rail type direct-injection diesel engine in the same manner as described above, the particulates were trapped/collected, and a relation of the gap width of the void portion and the trapping/collecting efficiency in a given run time was checked.

[0051] Results are shown in FIG. 11. With the increase of the gap width of the void portion, the trapping/collecting efficiency gradually drops. However, even with the gap width of 0.8 mm, a practically sufficient trapping/collecting efficiency of 65% is attained (it is to be noted that when the void portion is not formed (gap width of 0 mm), the efficiency is 85%). When the gap width exceeds 0.8 mm, the trapping/collecting efficiency starts largely dropping. However, even with the gap width of 1 mm, the efficiency is 50%, and this is a practically usable region. With the gap width of the void portion exceeding 1 mm, much time is required until the void portion is closed by the deposited particulates, the trapping/collecting efficiency largely drops, and therefore this width is not practical.

[0052] Moreover, when the gap width of the void portion is less than 0.2 mm, the ashes are not sometimes discharged well. Therefore, the width is preferably 0.2 mm or more. Additionally, when the gap width of the void portion is less than 0.4 mm, the ashes are sometimes incompletely discharged in a low-speed run at 1000 rpm or less. On the other hand, when the gap width of the void portion is 0.4 mm or more, the ashes are substantially completely discharged even at the time of idling run, and therefore this width is more preferable.

[0053] From above, it can be said that the gap width of the void portion is in a range of preferably 0.2 to 1 mm, more preferably 0.4 to 0.8 mm.

[0054] As described above, with the use of a honeycomb structure of the present invention as a filter for trapping/collecting particulates included in an exhaust gas of internal combustion engines such as a diesel engine, different from a related art, it is possible to remove ashes deposited inside without requiring any special mechanism or apparatus or without detaching the filter from the exhaust system. According to a manufacturing method of the present invention, the above-described honeycomb structure can easily and economically be prepared. Furthermore, in an exhaust gas purification system of the present invention, with the use of the honeycomb structure as the filter, it is possible to easily remove the ashes deposited in the filter.

Claims

1. A honeycomb structure comprising:

a plurality of through channels extending to an axial direction of a honeycomb structure, porous partition walls separating through channels one another, and plugging portions; said plugging portion plugging predetermined through channels at one end and the rest of through channels at other end opposite to the plugged end of the predetermined through channels,

wherein at least a part of predetermined crossing portions of the porous partition walls is discontinued to form a void portion in each of the predetermined crossing portions.

2. The honeycomb structure according to claim 1, wherein the void portions are formed along a whole length of the honeycomb structure at predetermined positions at a regular interval.

3. The honeycomb structure according to claim 1 or 2, wherein a gap width of the void portion is in a range of 0.2 to 1 mm.

4. The honeycomb structure according to claim 1 or 2, wherein a gap width of the void portion is in a range of 0.4 to 0.8 mm.

5. The honeycomb structure according to any one of claims 1 to 4, wherein a gap width of the void portion at the vicinity of an outer peripheral portion of the honeycomb structure is larger than that of the void portion in a central portion seen from one of end faces of the honeycomb structure.

6. The honeycomb structure according to any one of claims 1 to 5, wherein a thickness of the partition wall having no void portion and extending without having a discontinued portion in a predetermined direction is larger than that of the partition wall having the void portion and a discontinued portion defined by the void portion in a section of the honeycomb structure crossing at right angles to a length direction.

7. The honeycomb structure according to claim 6, wherein the thickness of the partition wall having no void portion and extending without having a discontinued portion in the predetermined direction is 1.05 to 1.5 times that of the partition wall having the void portion and the discontinued portion defined by the void portion in the section of the honeycomb structure crossing at right angles to the length direction.

8. The honeycomb structure according to claim 6, wherein the thickness of the partition wall having no void portion and extending without having a discontinued portion in the predetermined direction is 1.1 to 1.3 times that of the partition wall having the void portion and a discontinued portion defined by the void portion in the section of the honeycomb structure crossing at right angles to the length direction.

9. The honeycomb structure according to any one of claims 1 to 8, wherein a sectional shape of the through channel is any one of a triangular shape, a quadrangular shape, a hexagonal shape, and a circular shape.

10. The honeycomb structure according to any one of claims 1 to 8, wherein a sectional shape of the through channel is a quadrangular shape, the void portion is regularly formed at every other crossing portion of partition walls disposed adjacent to one another, and only one gap is formed by the void portion in each of predetermined through channels.

11. The honeycomb structure according to claim 1, wherein the honeycomb structure is made of a material, as a major crystal phase, containing any one selected from the group consisting of cordierite, silicon carbide, silicon nitride, alumina, mullite, and LAS.

12. A use of a honeycomb structure according to any one of claims 1 to 11 as a filter for trapping/collecting/removing particulate materials included in dust-containing fluids such as an exhaust gas of an internal combustion engine by virtue of a filterability of the partition walls.

13. A method for manufacturing a honeycomb structure according to claim 1, which comprising the steps of:

preparing a die for extruding a honeycomb structure having slits for forming void portions in an intended manner when a honeycomb structure is extruded, and
extruding a honeycomb structure having a plural number of void portions in at least a part of the predetermined crossing portions of partition walls.

14. An exhaust gas purification system for trapping/collecting/removing particulate materials containing carbon as a major component included in dust-containing fluids such as an exhaust gas of an internal combustion engine, the system comprising:

a honeycomb structure according to any one of claims 1 to 12; and
heating means for burning the particulate materials trapped/collected by the honeycomb structure to regenerate a filtering capacity thereof,

wherein the void portion of the honeycomb structure has such a construction that the void portion is closed due to accumulated trapped/collected particulate materials during actual run, thus closed void portion is reopened by burning particulate materials accumulated by heating for the regeneration thereof, and at least some of unburnt materials such as ashes deposited in the honeycomb structure is discharged from the honeycomb structure together with a flow of dust-containing fluids, when the void portion is reopened.

15. The exhaust gas purification system according to claim 14, wherein the heating means is any one of an electric heater, a burner using a gas or liquid fuel, a microwave generation apparatus, and heating means for discharging

EP 1 413 356 A1

unburnt fuel components in the exhaust gas of the internal combustion engine and for burning the unburnt fuel components by a catalytic reaction to raise an exhaust gas temperature.

5

10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8(a)




FIG. 8(b)




FIG. 9




FIG. 10





FIG. 11





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 25 6383

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 6 248 689 B1 (MANSON IAN) 19 June 2001 (2001-06-19) * figure 1 *	1,2, 12-14	B01J35/04 F01N3/022
X	EP 0 736 503 A (NIPPON DENSO CO) 9 October 1996 (1996-10-09) * figures 18,19 *	1,2, 12-14	
X	US 5 566 545 A (HIRAOKA TETSUYA ET AL) 22 October 1996 (1996-10-22) * figure 4 *	1,2, 12-14	
X	WO 93 21429 A (FLECK CARL M) 28 October 1993 (1993-10-28) * page 3, line 5 - line 11; figure 3 *	1,12-14	
X	EP 0 134 002 A (INTERATOM) 13 March 1985 (1985-03-13) * figures *	1,2, 12-14	
A	EP 1 219 794 A (DENSO CORP) 3 July 2002 (2002-07-03)		TECHNICAL FIELDS SEARCHED (Int.Cl.7) B01J F01N
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 27 February 2004	Examiner Schwallier, J-M
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (03/82) [P04C01]

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 25 6383

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-02-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6248689	B1	19-06-2001	US 6013599 A	11-01-2000
			AU 5000099 A	07-02-2000
			CA 2340624 A1	27-01-2000
			EP 1096990 A1	09-05-2001
			JP 2002520149 T	09-07-2002
			WO 0003790 A1	27-01-2000
EP 0736503	A	09-10-1996	JP 8332329 A	17-12-1996
			DE 69622307 D1	22-08-2002
			DE 69622307 T2	20-03-2003
			EP 0736503 A1	09-10-1996
US 5566545	A	22-10-1996	JP 7054632 A	28-02-1995
			JP 3078428 B2	21-08-2000
			JP 7054633 A	28-02-1995
			DE 4428214 A1	16-02-1995
WO 9321429	A	28-10-1993	WO 9321429 A1	28-10-1993
			AU 3817593 A	18-11-1993
EP 0134002	A	13-03-1985	DE 3330020 A1	28-02-1985
			AT 34804 T	15-06-1988
			DE 3471715 D1	07-07-1988
			EP 0134002 A1	13-03-1985
EP 1219794	A	03-07-2002	JP 2002256842 A	11-09-2002
			EP 1219794 A1	03-07-2002
			US 2002078667 A1	27-06-2002

EPO FORM P0458

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)